


*Note: 800NMIMH new dual pin "Z" receivers accept only dual pin interchangeable heads.



CDI TORQUE PRODUCTS

INTERCHANGEABLE HEAD TORQUE WRENCHES

These interchangeable torque wrenches are designed for use on production lines and other applications where a specific torque is required for repetitive operations.

Features

- Interchangeable heads permit ratcheting, fixed, or open end torquing capability with adjustable torque wrench bodies.
- A push of the locking pin provides quick-change action, with a wide range of head styles to choose from.
- Micrometer Type Adjustment-ensures fast, accurate settings and changes.
- *Part Number 800NMIMH has Dual Pin Release for added strength

INTERCHANGEABLE HEAD TORQUE WRENCHES

Product Code	Shank Size	Increments	Nm	Ft. Lbs
			Torque Range	Torque Range
50NMIMH	J	0.5	10 - 50	7.4 - 44.2
100NMIMH	J	0.5	20 - 100	14.8 - 73.8
200NMIMH	Y	2	40 - 200	29.5 - 147.5
350NMIMH	X	2	70 - 350	44.3 - 250.8
800NMIMH*	Z	5	150 - 800	110.6 - 590
75MFIMHSS	J	0.5	N/A	5 - 75
150MFIMHSS	Y	1	N/A	20 - 150
250MFIMHSS	Y	1	N/A	30 - 250



CDI TORQUE PRODUCTS

PRE-SET TORQUE WRENCHES

Pre-Set torque wrenches are designed for use on production lines and other applications where a specific torque is required for repetitive operations.

Features

- Featuring a durable, non-slip cushion grip
- Uses universal round shank heads
- Audible click and feel impulse torque control mechanism
- Tamper proof torque setting for production line use
- Accuracy: $\pm 4\%$ of indicated value, in direction of torque indicator, from 20% to 100% of full scale
- Meets or exceeds ASME B107.14-2004, ISO 6789
- Calibration certificate available at additional cost

PRE-SET TORQUE WRENCHES

Product Code	English Range	Nm Range	Shank Size	A In.	B In.	C In.	D In.	Wt. Lbs.
5T-I	10 - 50 in.lb.	1.1 - 5.6 Nm	J	6.5	0.63	0.61	1	0.35
10T-I	50 - 250 in.lb.	5.6 - 28 Nm	J	10	0.63	0.61	1	0.55
10ST-I	60 - 300 in.lb.	6.8 - 34 Nm	J	6.2	0.68	0.86	1.4	0.75
50T-I	15 - 75 ft.lb.	20 - 102 Nm	J	11	0.68	0.86	1.4	1.4
100T-I	30 - 150 ft.lb.	41 - 203 Nm	Y	19.5	0.94	0.86	1.4	2.3
200T-I	40 - 200 ft.lb.	54 - 271 Nm	Y	23.5	0.94	0.86	1.4	2.6
300T-I	100 - 300 ft.lb.	135 - 406 Nm	X	27.7	1.12	1	1.4	3.9
600T-I*	120 - 600 ft.lb.	162 - 814 Nm	Z	55	1.5	1.25	1.25	10.45

*NOTE: No grip supplied.

